



Sato WT4-AXB – Kompakter und benutzerfreundlicher Industriedrucker



Kompakter 4-Zoll-Industriedrucker für vielfältige Medientypen

Etikettenrollen mit einem Außendurchmesser von bis zu 8 Zoll und Farbbänder mit einer Länge von bis zu 450 m



Intuitive Bedienung über 3,5-Zoll-Farb-LCD

Mehrsprachige Anzeige, farbcodierte Statusmeldungen und einfache Navigation



Vielseitige Anschlussmöglichkeiten für flexible Integration

USB, Ethernet, RS-232C standardmäßig; optional WLAN und Bluetooth



Einfache Wartung ohne Werkzeuge

Werkzeugloser Austausch von Druckkopf und Plattenwalze für minimale Ausfallzeiten



Umfangreiche Barcode- und Schriftsätze und mehrere Emulationen

Für eine einfache Integration in bestehende Systeme

Eigenschaften

Drucktechnologie: Thermodirekt und Thermotransfer

Druckbreite (max.): 4,09 Zoll (104 mm)

Druckauflösung (max.): 203 dpi oder 300 dpi

Druckgeschwindigkeit (max.): 203 mm/s (203 dpi), 152 mm/s (300 dpi)

Medientypen: Rollen- oder Leporello-Etiketten, Normalpapier, Endlospapier, Tag, Ticket

Sensoren: Einstellbarer I-Marken-Sensor (reflektierend), Etiketten-Gap-Sensor (transmissiv), Abdeckung offen und Farbband-Ende-Sensor

Druckersprachen: SBPL, SZPL, SIPL

Konnektivität: USB 2.0 (Typ A & B), Ethernet, RS-232C; optional WLAN, Bluetooth

Display: 3,5-Zoll-Farb-LCD

Betriebstemperatur: 4 – 40 °C

Abmessungen (B x T x H): 268 x 445 x 261 mm

Gewicht: 11,4 kg

Optionales Zubehör

Dispenser

Full cutter

Dual WLAN und Bluetooth Schnittstelle

PRINTING SPECIFICATION			WT4-AXB (203 dpi)		WT4-AXB (300 dpi)	
Printing Method			Thermal Transfer			
Print Resolution			8 dots / mm (203 dpi)		12 dots / mm (300 dpi)	
Max. Print Area	Width mm (inch)		104mm (4.09")		104mm (4.09")	
	Length mm (inch)		996mm (39.33")		996mm (39.33")	
Print Speed, mm/sec (ips)			Up to 203.2mm/sec (8 ips)		Up to 152.4mm/sec (6 ips)	
CPU			32-bit RISC Microprocessor			
Printer Memory			Flash ROM: 128MB, DRAM: 128MB User Memory: 32MB External USB User Memory: 16GB			
CONSUMABLES SPECIFICATION						
Sensor Type			Adjustable I-Mark Sensor (Reflective) /Label Gap Sensor (Transmissive), Label Taken sensor, Head Open sensor, Ribbon Out Sensor			
Media Type			Roll or fan-fold die cut labels, Plain paper face stock, Continuous stock, Tag, Ticket			
Media Thickness			0.08 – 0.19mm (0.003" – 0.007")			
Label Shape	Diameter		Roll Max. outside diameter: Ø 203.2mm (8"), Core diameter: 76mm /38mm (3" / 1.5")			
	Wind Direction		Face-in / Face out			
Label Size	Continuous	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")	
		Length	6 – 2497mm (0.24" – 98.3")		6 – 1497mm (0.24" – 58.9")	
	Tear-Off	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")	
		Length	22 – 2497mm (0.86" – 98.3")		22 – 1497mm (0.86" – 58.9")	
	Cutter	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")	
		Length	22 – 2497mm (0.86" – 98.3")		6 – 1497mm (0.24" – 58.9")	
	Dispenser	Width	22 – 112mm (0.86" – 4.4")		22 – 112mm (0.86" – 4.4")	
		Length	22 – 397mm (0.86" – 98.3")		22 – 2497mm (0.86" – 98.3")	
Ribbon TT Model	Length		Max. 450 metres. Max Diameter 82mm			
	Width		40mm - 110mm (1.57" – 4.33")			
	Core Diameter		25mm (1")			
	Wind Direction		Face-in / Face-out			
FONTS / SYMBOLOGIES						
Internal Fonts Unicode supported	Standard Bitmap		Bitmap Fonts XS, XU, XM, XB, XL, OCR A, OCR B			
	Scaleable fonts		CG Times, CG Triumvirate, SUD-SON, SUD-HEI			
Barcode	1D Barcode		UPC-A/E, JAN/EAN-8/13, Code 39, Code 93, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, MSI, GS1 Databar: Omni, Truncated, Stacked, Stacked Omni, Limited, Expanded, Expanded stacked. UPC Add-on, Postnet, Industrial 2 of 5. Composite: JAN/EAN-8/13, UPC A/E, GS1 Databar, Truncated and Stacked			
	2D Barcode		PDF417 including Micro pdf, MAXI Code, QR Code, GS1 Data Matrix (ECC200), Aztec			
Print Rotation	Character Data / Barcode		0°, 90°, 180°, 270°			
COMMUNICATION INTERFACES						
Interfacing			Standard: USB Type A 2.0 + USB Type B 2.0 + LAN + RS-232 Options: Wireless LAN b/g/n and Bluetooth			
			LAN protocols: ARP, IP, ICMP, UDP, TCP, HTTP, DHCP, Socket, LPR, SNMPv1.2			
Command languages (Printer language emulations)			SBPL SATO Barcode Printer Language, SZPL, SIPL			
OPERATING CHARACTERISTICS						
Power Requirements			Input voltage: AC100V-240V +/- 10% (full range)/ Frequency 50HZ -60Hz +/- 5%			
Environment	Operating		4 – 40°C / 30 – 80% RH (without condensation)			
	Storage		-20 - 50°C / 15 - 85% RH (without condensation)			
Dimension (W x D x H)			267.7 x 450 x 261mm *(H1 Opcional: 256mm) - 10.54" x 17.71" x 10.30" *(H1 Opcional 10.01")			
Weight			11.4 kg (25.13 lb)			
Indicators, Buttons, Display			3 blue colour LED indicators , 7 x Buttons, 3.5" Color LCD			
MISCELLANEOUS						
Certifications			FCC, UL, CSA, CE, TUV GS, ROHS 2.0 compliant, WEEE compliant			
Self-diagnostics			Error detection functions, Printhead overheat function			
Ease of service			Thermal printhead and Platen roller easily replaced			
OPTIONS & MANAGEMENT						
Accessories			Dispenser, Full cutter, Dual Wireless LAN and Bluetooth Interface			
Printer management			SATO Settings Utility for printer, network & Wireless configuration. SNMPv1.2 USB firmware upgrading			
SATO SUPPORT						
A full range of SATO-manufactured labels, tags and ribbons. SATO Value Support after-sales maintenance						