Zebra ZQ200 Serie

Zebra ZQ200 Serie – Einstieg in den mobilen Etikettendruck

Klein und leicht, kann überall hin mitgenommen werden
Extrem leicht und kompakt, ideal für mobile Arbeitsumgebungen ohne die Bewegungsfreiheit der Anwender zu beeinträchtigen.

Etiketten mit oder ohne Trägermedium bis zu einer Breite von 80 mm bedrucken
Diese Vielseitigkeit macht den Drucker ideal für verschiedenste Anwendungsfälle – von Preisetiketten im Einzelhandel bis zu Versandetiketten und Quittungen.

Großer Medienbehälter und einfache Medienwechsel

Die Benutzer können Medienwechsel ohne Werkzeug oder komplexe Schritte durchführen, was die Ausfallzeiten im Betrieb minimiert.

Bluetooth-Kopplung mit einem kompatiblen Gerät mittels NFC
Die NFC-Technologie erleichtert die schnelle Bluetooth-Kopplung mit kompatiblen Geräten, sodass der Drucker unkompliziert mit Android-, iOS- und Windows-Geräten verbunden werden kann.

Gegen Stürze aus bis zu 1,5 Metern geschützt
Die ZQ200 Serie ist für Stürze bis 1,5 Meter gesichert und besitzt die Schutzklasse IP43, die durch ein optionales Softcase auf IP54 erweitert werden kann.

Zebra ZQ200 Serie

Eigenschaften

Drucktechnologie: Thermodirekt

Druckbreite (max.): 58 / 80 mm

Druckauflösung: 203 dpi

Druckgeschwindigkeit (max.): 60 mm/s

Medienbreite & -stärke (max.): 48 / 72 mm, 0,05 mm

Medientypen: Etiketten, Belege

Mediensensor: Blackmark, Durchlicht, Medienende

Display: OLED

Kompatibel mit: Android, Apple iOS, Windows Mobile

Druckersprachen: CPLC, ESC-POS

Netzwerkverbindungen: Bluetooth, USB, NFC

Akku: 1500 / 2550 mAh, wechselbar

Schutz: IP43, sturzsicher bis 1,5 m

Betriebstemperatur: -10 – 50°C

Abmessungen (B x L x H): 118 x 85 x 44 / 129 x 114 x 56 mm

Gewicht: 265 / 420 g

Optionales Zubehör

5-fach Docking-Station (ZQ210)

3-fach Akku-Ladestation (ZQ220)

Zusatz-Akku

Tragetasche

Softcase

Schultergurt

Gürtelclip

Fahrzeughalterung

Wechselstromadapter

Zebra ZQ200 Serie

barcotec
YOUR DIGITAL ENABLING SPECIALIST.

Physical Characteristics	
Dimensions	ZQ220: 129.5 mm L x 114.5 mm W x 56.7 mm H 5.0 in. L x 4.5 in. W x 2.2 in. H ZQ210: 118 mm L x 85.5 mm W x 44.5 mm H 4.65 in. L x 3.35 in. W x 1.75 in. H
Weight (with battery)	ZQ220: 420 g/0.92 lbs ZQ210: 265 g/0.58 lbs
Printer Specifications	
Programming Languages	CPCL and ESC-POS languge
Resolution	203 dpi/8 dots per mm
Memory	16MB SDRAM, 16MB Flash
Max Media Width	ZQ220: 72 mm/2.83 in. ZQ210: 48 mm/1.89 in.
Max Print Speed	ZQ220: 2.5 ips (60 mm/s) ZQ210: Receipt and Label: 2.5 ips (60 mm/s) Linerless: 2 ips (50 mm/s)
Sensors	Black Mark, Gap, Media Out sensing
Battery Capacity and Type	ZQ220:2550 mAh (7.4V), rechargeable Li-ion battery ZQ210: 1500 mAh (7.4V), built-in rechargeable Li-ion battery
Media Characteristics	
Media Type	Direct Thermal media, continuous receipt, black mark receipt, and gap label, option for linerless label
Media Width	ZQ220: 80 mm/3.15 in. 76.2 mm/3.00 in. 58 mm/2.28 in. 50.8 mm/2.00 in. ZQ210: 58 mm/2.28 in. 50.8 mm/2.00 in. 40 mm/1.57 in. 30 mm/1.18 in.
Media Roll Diameter	ZQ220: **Inner:** 12.7 mm/0.5 in. **Outer:** 50 mm/2.0 in. ZQ210: **Inner:** 12.7 mm/0.5 in. **Outer:** 40 mm/1.57 in.
Media Thickness	0.05334 mm / 0.0021 in.
Minimum Label/ Receipt Length	12.5/0.49 in.
Maximum Label/ Receipt Length	Unconstrained in line print mode
Environment and Resistance	
Operating Temp.	-10°C to 50°C/14°F to 122°F
Storage Temp.	-20°C to 60°C/-4°F to 144°F
Charging Temp.	-0°C to 40°C/32°F to 104°F
Charging Time	3.5 Hours (23 °C +/- 5°C)
Printing Length per Charge	Minimum of 500 labels x 8.5 in. length, 13% density
Drop Specification	1.5 m/5 ft. to concrete
IP Rating	IP43 (IP54 with case)

Agency Approvals	
Emissions	EN55032, ETSI EN 301 489 -1 / -17
Susceptibility	EN55035, ETSI EN 301 489 -1 / -17
Safety	EN60950, EN62368
Communication and Interface	
Bluetooth	Bluetooth 2.1+EDR/4.1 Low Energy dual mode
USB Port	USB 2.0 type-C connector
NFC Tag	Passive NFC tag
Charging Method	USB and/or docking charging
Low Power Mode	Support power saving
MFi (iOS support via Bluetooth)	MFI -Certified
User Interface	OLED Screen, Control Buttons (Power, Config, Feed)
Fonts	
Built-in fonts (bitmap)	CPCL fonts: English/Latin9, Cyrillic, ESC-POS Font: Font A: 12X24 Font B: 9x17 Font C: 9x24 (CPCL fonts: ROA SKU) traditional Chinese M Kai 24x24, New Sans MT 16x16, Vietnamese 16x16
Barcode Symbology	
Linear Barcodes	Code 39, Code 93, UCC/EAN128 (GS1-128), Code 128, Codabar, Interleaved 2-of-5, UPC-A and UPC-E 2, 5 digit add-on and composite, EAN-8, EAN-13, 2, 5 digit add-on and composite
2D Barcodes	PDF417, MicroPDF417, MaxiCode, QR Code, GS1/ DataBar™ (RSS) family, Aztec, MSI/Plessey
Software and Tools	
SDK	ZebraLink, legacy Multiplatform SDK support for PC Windows v7, v8, v10, Android, iOS, Windows CE, Windows® Mobile 6.5
Tools	Zebra PC Setup Utility, OPOS Driver, Zebra NetBridge, Zebra Designer (Printer Windows Driver, Font and Graphic Downloader, Status Monitor, Label Design Application)
Printer Set-Up Utility	The free Printer Setup Utilities simplifies printer configuration and uncovers security vulnerabilities using the Android and iOS versions of the utility.