



ProGlove Basic – Ideal für die Logistik und Retail

- ✓ Produkte und Pakete mit beiden Händen bearbeiten

Der ProGlove Basic wird am Handrücken getragen und ermöglicht das Scannen von Barcodes, ohne dass ein separates Gerät gehalten werden muss. Dies steigert die Produktivität, da beide Hände für andere Aufgaben frei bleiben.

- ✓ Anbindung an Mobiles, Tablets und Terminals mittels stromsparenden Bluetooth LE

Mit einer Reichweite von bis zu 10 Metern können auch stationäre Geräte problemlos angebunden werden.

- ✓ Zwei Lesereichweiten für verschiedene Abstände

Standard-Range: Liest Barcodes aus Entfernungen von 10 bis 80 Zentimetern. Mid-Range: Geeignet für Distanzen von 30 bis 150 Zentimetern. Der Scanwinkel kann dabei bis zu 60 Grad betragen, was vielseitige Einsatzmöglichkeiten bietet.

- ✓ Leichtes und robustes Design für den täglichen Einsatz

Der ProGlove Basic wiegt nur 40 Gramm und bietet eine IP43-Zertifizierung, die ihn vor Staub und Spritzwasser schützt.

- ✓ Befestigung auf Manschetten mit Zeigefinger-Trigger

Der ProGlove Basic wird auf Manschetten mit einem Zeigefinger-Trigger befestigt. Diese sind in verschiedenen Größen für Rechts- und Linkshänder erhältlich, was eine komfortable und individuelle Anpassung ermöglicht.

Eigenschaften

Lesbare Codes: 1D, 2D, Post

Leseabstand: ca. 10 - 80 / 30 - 150 cm

Feedback: Licht, Ton & Vibration

Akku: ca. 3000 Scans

Konnektivität: Bluetooth Low Energy, bis zu 20 m

Schutz: IP43, bis 2 m sturzsicher

Betriebstemperatur: 0 - 50 °C

Abmessungen (B x L x H): 50 x 45 x 16 mm

Gewicht: 40 g

Optionales Zubehör

Longlife - Index Trigger

Reel

2-fach Ladestation

10-fach Ladestation

Gateway

WIRELESS COMMUNICATION
BLUETOOTH LOW ENERGY

BLUETOOTH RADIO	Supports Bluetooth Low Energy 4.0, 4.1, 4.2, 5.0	
TRANSMISSION RANGE	3rd party device Free field: 40 m (131 ft)** Indoor: 10-20 m (33-66 ft)**	ProGlove Gateway Free field: 70 m (230 ft)** Indoor: 30-40 m (100-130 ft)**
	**may decrease in industrial environments (e.g. due to walls, metal shelving, machines)	

BARCODE DECODING CAPABILITIES

1D	Auto decodes all standard 1D codes including GS1 DataBar linear codes et al.
2D	PDF417, MicroPDF417, Data matrix, QR Code, Micro QR Code, Aztec, MaxiCode et al.
POSTAL	US PostNet, US Planet, UK Postal, Australia Postal, Japan Postal, Dutch Postal (KIX) et al.

ELECTRICAL PROPERTIES

BATTERY	335 mAh, Lithium polymer (rechargeable)
CHARGING TIME	2 hours with ProGlove Charging Station
OPERATING TIME / SCANS	Approx. 5000 scans depending on the application and environmental conditions

MECHANICAL PROPERTIES

DIMENSIONS	50 x 45 x 16 mm (1.47 x 1.77 x 0.63 in)
WEIGHT	40 g (1.41 oz)

ENVIRONMENTAL CONDITIONS

DROP RESISTANCE	Resists 50 drops from 2 m (6.5 ft) onto concrete
PROTECTION AGAINST DUST AND WATER	IP43
TEMPERATURE	Operating Temperature: 0°C - 50°C (32°F - 122°F) Charging Temperature: 5°C - 40°C (41°F - 104°F) Storage Temperature: -20°C - 60°C (-4°F - 140°F)
HUMIDITY	5% - 95% non condensing
ELECTROSTATIC DISCHARGE (ESD)	±8kVdc air discharge ±4kVdc contact discharge

INTERFACES

BLUETOOTH	HID Profiles
ANDROID	HID, Insight Mobile (Android) (App/SDK)
IOS	HID, Insight Mobile (iOS) (SDK)
USB	ProGlove Gateway

SCANNER PROPERTIES

READING FIELD OF VIEW	Standard range: horizontal: 48°, vertical: 36.7° Mid range: horizontal: 31°, vertical: 23°
SKEW, PITCH & ROLL	Skew tolerance: ±60° Pitch tolerance: ±60° Roll tolerance: 360°
AMBIENT LIGHT	0 - 96,900 lux
AIMER	650 nm, 1 mW

SCAN RANGES

Minimum distance determined by symbol length, scan-angle and environmental conditions.

STANDARD RANGE

The smallest symbol in the barcode (the mil-inch (mm) number indicates the size of the smallest function in the barcode)	Possible distance between user and barcode
3 mil code 39	2.8 in./7.1 cm to 6.2 in./15.8 cm
5 mil code 128	2.3 in./5.8 cm to 8.7 in./22.1 cm
5 mil code PDF417	3.0 in./7.6 cm to 8.1 in./20.6 cm
10 mil DataMatrix	2.4 in./6.1 cm to 10.6 in./26.9 cm
100% UPCA	1.6 in./4.1 cm to 23.0 in./58.4 cm
20 mil code 39	1.6 in./4.1 cm to 36.3 in./92.2 cm

MID RANGE

5 mil (0.127 mm) code 128	7.4 in./18.8 cm to 16.0 in./40.6 cm
5 mil (0.127 mm) PDF417	8.1 in./20.6 cm to 13.1 in./33.3 cm
10 mil (0.254 mm) DataMatrix Example: A 10 mil DataMatrix symbol, which can carry 25 alphanumeric characters, has a size of 4.57 mm * 4.57 mm	7.0 in./17.8 cm to 17.0 in./43.2 cm
100% UPCA	2.3 in./5.8 cm to 38.0 in./96.5 cm
20 mil (0.508 mm) code 39	2.1 in./5.3 cm to 54.0 in./137.2 cm
100 mil (2.54 mm) code 39	11.0 in./27.9 cm to 172.0 in./436.9 cm

UTILITIES & ACCESSORIES*

CONFIGURATION & DEVICE MANAGEMENT	https://insight.proglove.com
DEVELOPER DOCUMENTATION	https://developers.proglove.com
ANDROID INTEGRATION	Insight Mobile (Android): Provides a full featured integration for Android enterprise applications.
IOS INTEGRATION	Insight Mobile (iOS): Provides an SDK for basic integration for iOS enterprise applications.
GATEWAY INTEGRATION	ProGlove Gateway: Hardware connector to enable the full capabilities of the ProGlove Ecosystem via USB-Interface.
TRIGGER	Scanner can be triggered only with ProGlove wearables (REEL, Index-Trigger et al.)

*More Information on www.proglove.com

WARRANTY & SLA

WARRANTY	12 months factory warranty
PROGLOVE CARE	36 and 60 months maintenance contracts available. For more information please contact your ProGlove representative or visit https://proglove.com

SAFETY & REGULATORY

RADIO AND ELECTROMAGNETIC COMPATIBILITY	EU: 2014/53/EU Radio Equipment Directive (RED) FCC ID: 2A0JL-MARK-2 IC: 23450-MARK2
ELECTRICAL SAFETY	EU: acc. to 2014/53/EU Radio Equipment Directive (RED) EN 62368-1:2014 + A11:2017 INTERNATIONAL: IEC 62368-1:2014 US: UL 62368-1, 2 nd Ed, 2014-12-01 and CAN/CSA C22.2 No. 62368-1-14
LED CLASSIFICATION	Standard Range: Excluded risk group LED product according to IEC/EN 62471
LASER CLASSIFICATION	Mid Range: According to EN 60825-1: 2014 and IEC 60825-1 (Ed. 3.0) Laser class 2 device. Caution Laser Radiation - Do not stare into beam.
ENVIROMENTAL	RoHS Directive 2011/65/EU; Amendment 2015/863, REACH SVHC 1907/2006; WEEE