



## Denso SC1-QB – Compact barcode scanner for the healthcare sector

- ✓ Seamless housing made of special plastic for cleaning with strong disinfectants
- ✓ Particularly small and light: Only 13 cm high and 130 g in weight
- ✓ Fast and reliable scanning of 1D and 2D codes, data transmission via Bluetooth 5.0 LE
- ✓ Withstands up to 2000 drops from 0.5 meters, protected against dust and water
- ✓ Charged in just 3 minutes for 30 minutes of continuous scanning

## Features

---

**Readable codes:** 1D & 2D codes

---

**Target marking:** LED

---

**Feedback:** LED, beeper and vibration

---

**Connectivity:** Bluetooth 5.0 LE

---

**Battery:** Capacitor battery, 3 min charging for 30 min continuous scanning

---

---

**Protection:** IP65, drop-proof up to 2 m

---

**Operating temperature:** -20 - 50 °C

---

**Dimensions:** 130 x 90 x 63 mm

---

**Weight:** 130 g

---

## Optional accessories

---

**Additional base station**

---

Typ		2D Scanner	
Scanner	Scanner-funktionen	2D Codes	QR Code, SQRC, Micro QR Code, DataMatrix(ECC200), PDF417, MicroPDF417, MaxiCode, Aztec, GS1 Composite
		Barcodes	EAN-13/8 (JAN-13/8), UPC-A/E, UPC/EAN (with add-on), Interleaved 2 of 5, Standard 2 of 5, Codabar (NW-7), CODE39, CODE93, CODE128, GS1-128 (EAN-128), GS1 DataBar (RSS)
	Mindest-auflösung	2D Codes	0,127 mm
		Barcodes	0,076 mm
	PCS Wert		Mehr als 0,3
	Marker		LED
	Winkel		±50°
	Neigungswinkel		360°
Kommunikati-onsschnittstelle	Lesebestätigung		LED Licht (Blau, grün und rot), Ton und Vibration
	Methode		Bluetooth Ver. 5.0 Low Energy
Stromversor-gung	Stromversorgung		Kondensator Batterie (Kabelloses Laden an der Basis, separat erhältlich)
	Ladezeit		ca. 3 Minuten
	Betriebsdauer		ca. 30 Minuten (1 Scan pro 5 Sek.)
Umgebungsbe-dingungen	Schutzart		IP65
	Temperatur		-20 bis 50°C
	Luftfeuchtigkeit		10 to 90 %RH (nicht kondensierend und nicht vereisend)
	Sturzfestigkeit		2.0m (auf Betonboden) / 0.5m×2,000 Mal
Gewicht		ca. 130 g	

