



Sato CL4NX Plus – Highest precision and customizability

- ✓ Precise printing from micro labels to large formats
- ✓ High printing speed in continuous operation
- ✓ Large media capacity for uninterrupted work
- ✓ Customized applications and easy integration of peripheral devices
- ✓ Color display and video instructions for easy operation

Features

Printing technology: Direct thermal / thermal transfer

Print width (max.): 4.09 inches (104 mm)

Print resolution (max): 609 dpi (automatic switching)

Print speed (max.): 355 mm/sec.

Media types: Roll labels, plain paper, synthetic paper or continuous paper

Sensors: Label gap sensor (transmissive) and I-mark sensor (reflective)

Printer languages: Auto Detect | SZPL, SDPL, SIPL, STCL, SEPL

Connectivity: USB, Ethernet, RS-232-C, IEEE 1284, EXT, NFC, external I/O, WLAN, Bluetooth

Display: 3.5-inch, color

Operating temperature: 0 to +40 °C

Dimensions (W x D x H): 271 x 457 x 321 mm

Weight: 15.1 kg

Optional accessories

Cutting device

Linerless cutting device

Dispensing device with integrated liner
rewinder

Real-time clock

Wireless LAN

Barcode checker stand

External rewind

External cover

RFID UHF & HF

Rotary cutter

PRINTING SPECIFICATION					
Printing Method		Direct Thermal / Thermal Transfer			
Print Mode		Continuous, Tear-off, Cutter, Dispenser, Linerless			
Print Resolution		8 dots/mm (203 dpi)	12 dots/mm (305 dpi)	24 dots/mm (609 dpi)	
Max. Print Speed		14 ips (355 mm/sec)	14 ips (355 mm/sec)	6 ips (152 mm/sec)	
Max. Print Area	Width	104 mm (4.09")			
	Length	2500 mm (98.42")	1500 mm (59.05")	400mm (15.75")	
Processor		Dual CPU & Dual OS: CPU1: 800MHz for Linux OS, CPU2: 800MHz for ITRON OS			
Printer Memory		CPU1: 2GB ROM, 256MB RAM, CPU2: 4MB ROM, 64MB RAM			
CONSUMABLE SPECIFICATION (Recommended to use consumables manufactured or supplied by SATO)					
Sensor Type		I-mark Sensor (Reflective), Label Gap Sensor (Transmissive)			
Media Type		Fan-fold or roll die-cut labels, plain paper, synthetic paper or continuous paper			
Media Thickness		0.060 - 0.268 mm (0.0024" - 0.011")			
Label Shape	Diameter	Max. 265mm (10.43"), Chuck diameter: Ø76mm (3.0"), Ø101mm (4.0")			
	Wind Direction	Face In / Face Out. No Setting Change Required			
Label Size (Without Liner)	Continuous	Length	6 - 2497mm (0.24" - 98.30")	6 - 1497 mm (0.24" - 58.94")	6 - 397 mm (0.24" - 15.63")
		Width	22 - 128 mm (0.87" - 5.04")	22 - 128 mm (0.87" - 5.04")	22 - 128 mm (0.87" - 5.04")
	Tear-off/ Cutter	Length	17 - 2497mm (0.67" - 98.30")	17 - 1497 mm (0.67" - 58.94")	17 - 397 mm (0.67" - 15.63")
		Width	22 - 128 mm (0.87" - 5.04")	22 - 128 mm (0.87" - 5.04")	22 - 128 mm (0.87" - 5.04")
	Dispenser	Length	10 - 397mm (0.39" - 15.63") ¹⁾	10 - 397 mm (0.39" - 15.63") ¹⁾	10 - 397 mm (0.39" - 15.63") ¹⁾
		Width	22 - 128 mm (0.87" - 5.04")	22 - 128 mm (0.87" - 5.04")	22 - 128 mm (0.87" - 5.04")
	Linerless	Length	30 - 120 mm (1.18" - 4.72")	30 - 120 mm (1.18" - 4.72")	30 - 120 mm (1.18" - 4.72")
		Width	60 - 118 mm (2.36" - 4.65")	60 - 118 mm (2.36" - 4.65")	60 - 118 mm (2.36" - 4.65")
Ribbon	Size	Max. Length: 600 m (1968.5'). 450 m (1476.4') when ribbon width is 39.5 mm (1.55") Max. Roll Diameter: 90 mm (3.5"), Ribbon width: 39.5 mm (1.55") to 128 mm (5.04")			
	Other	Core diameter: Ø25.4mm (1"), Wind direction : Face In/ Face Out, No Setting Change Required			
FONTS / SYMBOLOGIES					
Internal Fonts	Standard Bitmap	U, S, M, WB, WL, XS, XU, XM, XB, XL, X20, X21, X22, X23, X24, OCR-A, OCR-B			
	Scalable Fonts	30 SATO Fonts, 2 Outline Fonts			
	Encoding	Majour Latin and Pan-European Code Pages (WGL4), GB18030 (simplified), KSX1001 (Korean), BIG5 (traditional), JIS, SHIFT-JIS, Unicode UTF-8 and UTF-16BE also supported			
Barcode	Linear	UPC-A/UPC-E, JAN/EAN-13/8, CODE39, CODE93, CODE128, GS1-128/UCC/EAN128), CODABAR(NW-7), ITF, Industrial 2 of 5, Matrix 2 of 5, MSI, POSTNET, UPC add-on code, BOOKLAND, USPS code, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Limited, GS1 DataBar Expanded, GS1 DataBar Expanded Stacked			
	2D Symbologies	QR Code, Micro QR Code, PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, Data Matrix (ECC200), Aztec Code, GS1QR Code and Composite Symbologies			
Print Direction		Character data rotation: 0°, 90°, 180°, 270°			
User Downloadable Fonts, Graphics or Formats		Maximum 100MB			
INTERFACE CHARACTERISTICS AND INTEGRATION					
Interfaces and protocols		USB 2.0 (Type A & B), RS232C, IEEE1284, EXT, NFC, Ethernet (IPv4/v6) supporting:TCP/IP, LPR, FTP, SNMPv3, NTP, HTTP, DHCPv4, Stateless Auto Configuration, Stateful Auto Configuration (DHCPv6)			
Optional Interface		Wireless LAN, WiFi Certified, WiFi Direct, IEEE 802.11 a/b/g/n/ac Dual Band (2.4GHz, 5GHz), Security: WEP, WPA, WPA2, Dynamic WEP, DHCP Option 81. Bluetooth Ver. 3.0			
Remote Access		SNMP Ver.3, HTTPs			
Supported printer protocols		Standard: SBPL (SATO Barcode Printer Language) Emulation Language: Auto detect - SZPL, SDPL, SIPL, STCL, SEPL			
OPERATING CHARACTERISTICS					
Power Requirements		AC100V ~ AC240V±10%, 50/60 Hz, Auto-ranging Power Supply			
Environment	Operating	0 - 40°C / 30 - 80% RH (without condensation)			
	Operating Linerless	5 - 35°C / 30 - 75% RH (without condensation)			
	Storage	-20 - 60°C / 30 - 90% RH (without condensation)			
Dimensions		271 mm (10.67") × 457 mm (18.00") × 321 mm (12.64")			
Weight		15.1kg (33.28 lbs)			
Display Panel		TFT Full Color LCD, 3.5"(320 x 240 RGB)			
MISCELLANEOUS					
Standards & Agency Approvals		Printers are globally certified			
Functions – Useful features		Micro Label Printing, SATO Application Enabled Printing, SATO Online Services, 18 User Guidance Videos on LCD, Space for Customized Videos, Multi Language Support LCD Message (31 Languages), Energy Saving, Large Status LED, Multiple Interfaces-Auto-Switching, USB Memory for Data Copy, PDF Direct Printing, SFPL, Status Return, Alarm Sound			
Functions – Self Diagnosis Checking		Thermal head check, Paper end detection, Ribbon end detection, Test print, Head lift detection			
OPTIONS					
Accessories		Cutter, Linerless Cutter, Dispenser with Internal Liner Rewinder, Real-Time Clock, Wireless LAN (AC), Barcode Checker, External Rewinder, External Cover, RFID UHF & HF, Rotary Cutter			