

Nicht mehr verfügbar! Wir empfehlen: Denso BHT-M70



Denso BHT-1700 Long Range – Maximum range

- ✓ 10 metre reading range for efficient scanning in high-bay warehouses
- ✓ Shatterproof 4 inch touch display and illuminated buttons
- ✓ Ergonomic grip for better target acquisition
- ✓ Sturdy construction withstands falls from up to 2 metres
- ✓ Modern Android operating system with advanced security and management options

Features

Display: 4 inch, 480 x 800 px, Asahi Dragontrail Glass

Keyboard: 30 keys, 4 triggers

Operating system: Android 7 / 8

Readable codes: 1D and 2D

Operating time / battery charge: approx. 20 - 30 h

Connectivity: WLAN, Bluetooth, USB

Additional features: GPS, Touch Trigger

Docking station interfaces: USB, LAN

Protection: IP67, drop-proof up to 2 m

Dimensions (W x L x H): 71 x 188.5 x 32.3 mm

Weight: 438 g

Optional accessories

Protective cover

Hip bag

Hand strap

High-capacity battery

Battery

1- & 4-fold battery charging station

1- & 4-fold way docking station

Display protection foil

Denso BHT-1700 Long Range

Model			BHT-1700QLWB-P	
OS			Android 7.1.2 (Nougat) / Android 8.1 (Oreo)	
CPU			1.3 GHz Quad-core	
Memory	RAM		2 GB	
	Flash ROM		16 GB	
Display	Number of dots*1		4.0 inch WVGA (480x800 pixels)	
	Display system		Liquid crystal dot matrix display (colour)	
	Backlight		White LED	
Scanner	Reading system		Autofocus-area sensor	
	Readable codes	2D codes	QR Code, PDF417, MicroPDF417, MaxiCode, DataMatrix (ECC200), GS1 Composite	
		1D codes	EAN-13/8(JAN-13/8), UPC-A/E, UPC/EAN (with add-on), Interleaved 2 of 5 (ITF), Standard 2 of 5 (STF), CODABAR (NW-7), CODE39, CODE93, CODE128, GS1-128 (EAN-128), GS1 DataBar (RSS)	
	Minimum resolution	2D codes	0.25 mm	
		1D codes	0.15 mm	
	Scanning reference position		100 mm	
	Marker		Area guide marker	
	Scan confirmation		Visual (blue LED), acoustic (speaker), and haptic (vibration)	
Keypad	Number of keys		31 keys (including power key) + 4 trigger keys	
	Touch panel		Asahi Dragontrail™ Pro - wet touch / gloved fingertip / stylus	
GPS			A-GPS/GLONASS	
Communi- cation	Wireless LAN*2	Compatible standards	IEEE802.11a/b/g/n compliant	
		Frequency band	IEEE802.11a/n: 5.2 GHz, 5.3 GHz, 5.6 GHz band, IEEE802.11b/g/n: 2.4 GHz band	
		Trans- mission distance*3	IEEE802.11a: indoors = approx.50m, IEEE802.11b/g/n: indoors = approx.75m, outdoors = approx.200m	
		Transmis- sion speed*3	IEEE802.11b: 11/5.5/2/1 Mbps, IEEE802.11a/g: 54/48/36/24/18/12/9/6 Mbps, IEEE802.11n: 65/58.5/52/39/26/19.5/13/6.5 Mbps	
		Access method	Infrastructure mode	
		Security	Encryption: WEP(40/128)/TKIP/AES, WPA authentication: WPA/WPA2, User authentication: PSK/EAP-TLS/PEAP	
	Wireless WAN	Compatible standards	-	
	Bluetooth®		V4.1+EDR/LE (Compatible Profile:GAP/SDAP/HSP/SPP/GOEP/OPP/HFP(AG1.5)/PAN/A2DP/ AVRCP/GAVDP/HID/PBAP/HOGP/MAP/GATT)	
	USB (DNWA Connector)		USB 2.0	
Card slot			Micro SDHC / SDXC, nanoSIM x2	Micro SDHC / SDXC
Power supply	Power (standard / extended)		Lithium-ion battery 2300 mAh (BT-110LA) / 3450 mAh (BT-110L)	
	Operating time*4	Standard battery	20 hours*6	
		High capaci- ty battery	30 hours*6	
NFC			-	
Camera (Autofocus)			-	
Environ- mental require- ments	Operating temperature*7		-20° to 50° C	
	Protection rating		IP67	
	Drop resistance*8		1.2 m x 60 times or more, 2 m	
Weight (incl. standard battery)			Approx. 438 g	