

Nicht mehr verfügbar! Wir empfehlen: Denso BHT-M70



Denso BHT-1700 – Large screen and easy-to-grip keyboard

- ✓ Large display for easy operation
- ✓ Easy-grip keyboard for reliable data entry
- ✓ Efficient barcode scanning in all environments
- ✓ Modern Android operating system with advanced security and management options
- ✓ Ergonomic design with high stability and long battery life

Features

Display: 4 inch, 480 x 800 px, Asahi Dragontrail Glass

Keyboard: 30 keys, 3 triggers

Operating system: Android 7 / 8

Readable codes: 1D and 2D, NFC

Operating time / battery charge: approx. 12 - 33 h

Connectivity: WLAN, Bluetooth, 4G LTE, USB

Additional features: GPS, 8MP camera, touch trigger

Docking station interfaces: USB, LAN

Protection: IP67, drop-proof up to 2.5 m

Dimensions (W x L x H): 71 x 188.5 x 32.3 mm

Weight: 298 - 308 g

Optional accessories

Battery with cover BT-170LAC

Battery without cover BT-110LA

High-Cap Battery with cover BT-170LC

High-Cap Battery without cover BT-110L

USB Cradle + 2. Battery CU-1700U

LAN Cradle CU-1700L

4-fold Charger CH-1700

4-fold Battery charger CH-1104

MicroUSB data cable for cradle SKOX3-KAB-USB

Direct cable USB BHT-1700-LS

Holster BHT-1700-HOB

Belt bag BHT-1200-WPC1

Belt bag „B“ BHT-1700B-WPC1

Belt bag „Q“ BHT-1700Q-WPC1

Stylus EZ-BHT1700-ST

Display protection film

Model			BHT-1700 QWBG-2		BHT-1700 QLWB-P	
OS			Android 7.1.2 (Nougat) / Android 8.1 (Oreo)*9			
CPU			1.3 GHz Quad-core			
Memory	RAM		2 GB			
	Flash ROM		16 GB			
Display	Number of dots*1		4.0 inch WVGA (480x800 pixels)			
	Display system		Liquid crystal dot matrix display (colour)			
	Backlight		White LED			
Scanner	Reading system		Area sensor		Autofocus-area sensor	
	Readable codes	2D codes	QR Code, PDF417, MicroPDF417, MaxiCode, DataMatrix (ECC200), GS1 Composite			
			MicroQR Code, SQRC®			
		1D codes	EAN-13/8(JAN-13/8), UPC-A/E, UPC/EAN (with add-on), Interleaved 2 of 5 (ITF), Standard 2 of 5 (STF), CODABAR (NW-7), CODE39, CODE93, CODE128, GS1-128 (EAN-128), GS1 DataBar (RSS)			
	Minimum resolution	2D codes	0.167 mm		0.25 mm	
		1D codes	0.125 mm		0.15 mm	
	Scanning reference position		100 mm			
	Marker		Area guide marker			
	Scan confirmation		Visual (blue LED), acoustic (speaker), and haptic (vibration)			
Keypad	Number of keys		31 keys (including power key)			
			+ 3 trigger keys		+ 4 trigger keys	
Touch panel			Asahi Dragontrail™ Pro - wet touch / gloved fingertip / stylus			
GPS			A-GPS/GLONASS			
Communication	Wireless LAN*2	Compatible standards	IEEE802.11a/b/g/n compliant			
		Frequency band	IEEE802.11a/n: 5.2 GHz, 5.3 GHz, 5.6 GHz band, IEEE802.11b/g/n: 2.4 GHz band			
		Transmission distance*3	IEEE802.11a: indoors = approx.50m, IEEE802.11b/g/n: indoors = approx.75m, outdoors = approx.200m			
		Transmission speed*3	IEEE802.11b: 11/5.5/2/1 Mbps, IEEE802.11a/g: 54/48/36/24/18/12/9/6 Mbps, IEEE802.11n: 65/58.5/52/39/26/19.5/13/6.5 Mbps			
		Access method	Infrastructure mode			
		Security	Encryption: WEP(40/128)/TKIP/AES, WPA authentication: WPA/WPA2, User authentication: PSK/EAP-TLS/PEAP			
	Wireless WAN	Compatible standards	4G LTE / 3G / GSM, VoLTE		—	
	Bluetooth®		V4.1+EDR/LE (Compatible Profile:GAP/SDAP/HSP/SPP/GOEP/OPP/HFP(AG1.5)/PAN/A2DP/AVRCP/GAVDP/HID/PBAP/HOGP/MAP/GATT)			
	USB (DNWA Connector)		USB 2.0			
Card slot			Micro SDHC / SDXC, nanoSIM x2		Micro SDHC / SDXC	
Power supply	Power (standard / extended)		Lithium-ion battery 2300 mAh (BT-110LA) / 3450 mAh (BT-110L)			
	Operating time*4	Standard battery	12 hours*5		20 hours*6	
		High capacity battery	18 hours*5		30 hours*6	
NFC			yes		—	
Camera (Autofocus)			Rear: 8MP		—	
Environmental requirements	Operating temperature*7		-20° to 50° C			
	Protection rating		IP67			
	Drop resistance*8		1.5 m x 60 times or more, 2.5 m		1.2 m x 60 times or more, 2 m	
Weight (incl. standard battery)			Approx. 308 g		Approx. 438 g	