



Flexible self-service kiosk for modern retail spaces



Powerful self-service kiosk in three versions

Available as a single-sided, double-sided or wall-mounted kiosk. Makes optimal use of space and allows for more terminals in a small area.



27-inch touch display in portrait format for intuitive customer guidance

Ideal for ordering and information applications with a clear, easy-to-read user interface.



Integrated receipt printer, barcode scanner and payment terminal

For a complete self-service station without additional hardware.



Powerful hardware platform with Windows, Linux or Android

The modern system architecture ensures smooth processes and stable performance – even with graphics-intensive user interfaces.



Remote control of important device functions for easier maintenance

Optionally, several kiosk functions can be monitored and controlled remotely – ideal for fast service without on-site intervention.

Features

Variants: Single-sided, double-sided or wall-mounted kiosk

Display: 27" HD (1920 x 1080), LED backlight

Touchscreen: PCAP multi-touch (10 points)

Audio: Internal speaker, headphone/microphone connection

Operating systems: Windows 11, Linux or Android

Processor: Intel Alder Lake-N 12th Gen / Media Tek Genio 700

Memory: 8 GB DDR5, 256 GB SSD, 2 slots (including 1 SATA) / 64 GB eMMC

Connectivity: Ethernet, USB, serial, Wi-Fi, Bluetooth

Barcode scanner: Datalogic 1500i

Receipt printer: ODP 444, Epson TM-M30 or Advantech TP-3260

Payment terminals: various models from Ingenico, Verifone and PAX

Cash drawer: supports 19 or 24 V, two cash drawers with Y-cable possible

Protection: Splash and dust proof

Operating temperature: 0 to +40 °C

Dimensions (W x D x L): Single: 39.3 x 18.5 x 178 cm / Double: 39.3 x 23.9 x 178 cm / Wall: 39.3 x 18.5 x 106 cm

Weight: Single: 70 kg (including base) / Double: 94 kg (including base) / Wall: 50 kg

Optional accessories

Status indicator (LED, 3 colours)

Power supply with remote control

SYSTEM		YUNO KIOSK 27"
Processor	INTEL Alder Lake-N 12 th Gen (N97 or i3 - N 305)	
Memory	DDR5 (8 GB in standard)	
SSD	NVME 256 GB (2 slots with 1 SATA)	
LCD	27" TFT Full HD (1920 x 1080)	
Touch screen	Flat & Edgeless PCAP Panel	
Android system	Please contact us	

OTHER SYSTEMS	
1D/2D Scanner	Datalogic 1500i
Printer	ODP 444, EPSON Tm-M30 or ADVANTECH TP-3260 thermal receipt printer
LED Lighting	USB electronic card control (3 colours)
Controlled power supply	option

INPUTS/OUTPUTS	
Serial ports	2 x RS-232 serial ports with optional power, + 5V or + 12V
USB	2 X USB 3.0 Side Panel + 2 x USB 3.0 I/O Panel + 4 x USB 2.0 I/O Panel + 1 x USB-C + Alt Mode Video + USB high speed + PD in / PD out + PD 3 A 20V in + PD out 3A, 5V
Ethernet / LAN	1 x Gigabit Ethernet with WOL, PXE boot 10/100/1000 Base-T
Cash Drawer	1 x cash drawer for + 19V or +24V drawer, dual drawer support with Y Cable
Audio	Internal loudspeaker, headphones / microphone jack
Android system	Please contact us

PAYMENT TERMINALS	
Ingenico	LANE 5000 / LANE 3000-3600 / IPP 350 / SELF 4000-2000
Verifone	P630 / P400 / VX820
PAX	S 300 / Q25 / IM30

MISCELLANEOUS	
CEM	CE Directive CEM 2014/30/EU (Class B)
Safety	CE Directive BT 2014/35/EU / CB Report
Operating temperature	5 - 35° C
Front Panel	Splash & Dust Resistant
Colours	Black (other colours upon request - minimum order quantity 100 units)
Compatible OS	Windows 11 IoT LTSC 2024, Windows 10 IoT Enterprise, Linux, Android 13 GMS
Dimensions (W x D x H)	single : 39.3 x 18.5 x 178 double : 39.3 x 23.9 x 178 wall : 39.3 x 18.5 x 106
Weight (kg)	single : 70 (incl. pedestal) double : 94 (incl. pedestal) wall : 50 kg
Options	Standing plate 78,5 x 78,5 x 1 cm / 49 kg Pedestal (single sided / double sided) Wall fixing kit (wall mounted)

SYSTEM		YUNO KIOSK 27"			
Processor	Media Tek Genio 700 (MT8390) processor				
Memory	8 GB				
GPU	Mali-G57 MC3				
Storage	64 GB eMMC				
LCD	27" TFT Full HD (1920 x 1080)				
Touch screen	Flat & Edgeless PCAP Panel				
OTHER SYSTEMS					
1D/2D Scanner	Datalogic 1500i				
Printer	ODP 444, EPSON Tm-M30 or ADVANTECH TP-3260 thermal receipt printer				
LED Lighting	USB electronic card control (3 colours)				
INPUTS/OUTPUTS					
USB	1 x USB-C, 1 x USB-C (PD out 12V@3A+USB 2.0), 1 x USB-C (OTG Support), 2 x USB 3.0 Type A				
WIFI & Bluetooth	802.11 a/b/g/n/ac/ax, Bluetooth 5.2 (BLE Supported)				
Ethernet	1 x RJ45 Giga LAN				
Audio	Internal loudspeaker				
PAYMENT TERMINALS					
Ingenico	LANE 5000 / LANE 3000-3600 / IPP 350 / SELF 4000-2000				
Verifone	P630 / P400 / VX820				
PAX	S 300 / Q25 / IM30				
MISCELLANEOUS					
CEM	CE Directive CEM 2014/30/EU (Class B)				
Safety	CE Directive BT 2014/35/EU / CB Report				
Operating temperature	5 - 35° C				
Front Panel	Splash & Dust Resistant				
Colours	Black (other colours upon request - minimum order quantity 100 units)				
OS	Android 13 GMS				
Dimensions (W x D X H)	single : 39.3 x 18.5 x 178	double : 39.3 x 23.9 x 178	wall : 39.3 x 18.5 x 106		
Weight (kg)	single : 70 (incl. pedestal)	double : 94 (incl. pedestal)	wall : 50 kg		
Options	Standing plate 78,5 x 78,5 x 1 cm / 49 kg Pedestal (single sided / double sided) Wall fixing kit (wall mounted)				