



Kompakte Effizienz für anspruchsvolle Aufgaben

-  **Schnelle Barcode-Erfassung mit Green Spot und DeepSight Decoding-Technologie**
Die innovative Halogen™ DE2121-DL Scan-Engine ermöglicht schnelles und zuverlässiges Scannen auch von beschädigten oder verschmutzten Barcodes. Dank GS1 Digital Link-Kompatibilität unterstützt das Gerät zudem die neuesten Barcode-Standards.
-  **Hochmoderne Konnektivität mit Wi-Fi 6/6E, Bluetooth 5.3 und 5G**
Ausgestattet mit dem Qualcomm QC4490 Octa-Core-Prozessor und bis zu 6 GB RAM ermöglicht die Memor 12/17-Serie schnelles Multitasking und optimale Datenverarbeitung.
-  **Rugged Design mit Corning Gorilla Glass 7, IP65/IP67 Schutz und MIL-STD-810H**
Die schlanke Bauform und das geringe Gewicht von 245 g sorgen für eine komfortable Nutzung über den gesamten Arbeitstag.
-  **Flexibles Laden: kabellos, USB-C und Ladestationen**
Mit einer austauschbaren 4000-mAh-Batterie ermöglichen die Geräte lange Betriebszeiten.
-  **Zukunftssichere Software und 4+4 Jahre Support**
Mit Android 13 und Upgrade-Möglichkeit bis Android 18 gewährleistet die Memor-Serie langfristige Nutzung und hohe Sicherheit.

Eigenschaften

Lesbare Codes: 1D, 2D, GS1 Data Link

Display: 6,0 Zoll FHD+ (1080 x 2160), Gorilla Glass 7, multitouch-fähig, 450 Nits Helligkeit

Betriebssystem: Android 13 GMS (auf bis zu Android 18 aufrüstbar)

Prozessor: Qualcomm QcX4490 Octa-Core 2,4 GHz

Speicher: 6 GB RAM (+2 GB Swap-Option), 64 GB Flash-Speicher, erweiterbar 2 TB via microSD

Feedback: Datalogic Green Spot für visuelle Bestätigung, Vibration, Ton

Tasten: 2 Seitenscan-Tasten, PTT-Taste, Ein/Aus, Lautstärke, 3 Android-Soft-Tasten

Kommunikation: Wi-Fi 6E, Bluetooth 5.3, 5G, NFC, USB-C

Zusätzliche Features: 13 MP Rückkamera mit Autofokus und LED-Blitz, 8 MP Frontkamera, GPS, div. Sensoren

Akku: 4000 mAh, kabelloses Laden (Qi-kompatibel)

Schutz: IP65/IP67, Sturzsicherheit bis 1,5 m mit Schutzhülle

Betriebstemperatur: -10°C bis 50°C

Abmessungen (B x L x H): 165 x 76,7 x 13,5 mm

Gewicht: 245 g (mit Akku)

Optionales Zubehör

Ein- und 4-fach-Dockingstationen (opt. mit kabellosem Laden)

Akku-Mehrfach-Ladestationen

Fahrzeughalterung mit Lademöglichkeit

Wearable Holder

Holster

Handschlaufe

Trigger Handle

Schutzhülle

Zusatz-Akkus

WIRELESS COMMUNICATIONS

Local Area Network (WLAN)	Wi-Fi 6e IEEE 802.11 a/b/g/n/ac/ax and 802.11 d/e/h/i/k/r/l/v/w/mc; Frequency range: Country dependent, typically 2.4 GHz, 5 GHz and 6 GHz bands; 2x2 MIMO; WPA3 Enterprise 192-bit mode supported
Personal Area Network (WPAN)	Bluetooth wireless technology v5.3 (Classic Bluetooth wireless technology and BLE)
NFC Communication	Support for the following standards: Tag types 1/2/3/4/5 (ISO 14443-4 A/B; ISO 15693; Mifare; Felica) Card emulator. Contactless payments and Apple ECP protocol supported.
WWAN / Cellular	Memor 17 LTE-Advanced / 4G+; NR 5G FR1; 3GPP Rel.16; • EMEA and ROW Configuration: GSM: Quad band; WCDMA: B1/2/4/5/8; FDD_LTE: B1/2/3/4/5/7/8/17/19/20/25/28/66; B34/38/39/40/41/42/43; 5G: n1/2/3/5/7/8/20/25/28/38/40/41/66/77/78/79; • North America Configuration (AT&T and Verizon certified): GSM: 850/1900; WCDMA: B2/4/5; FDD_LTE: B2/4/5/7/12/13/17/19/25/26/29/30/66; TDD_LTE: B38/41/48; 5G: N2/5/7/12/13/25/26/29/30/38/41/66/71/77; • VoLTE, VoNR and Wi-Fi calling enabled
Global Positioning System (GPS)	Integrated Assisted-GPS (A-GPS) Supported Types: GPS Dual Band, Galileo Dual Band, BeiDou Dual Band

ELECTRICAL

Battery	1-piece swappable battery pack with rechargeable Li-Ion batteries; 3.87V; 4,000 mAh typical (14.98 Watt-hours)
Wireless Charging	WPC Qi EPP compliant; 7W charging

ENVIRONMENTAL

Drop Resistance	Multiple 1.3/4ft drops to concrete across operative temperature without rubber boot per enterprise standard according to MIL STD 810H. Multiple 1.5m/6ft drops to concrete over operating temp (-20°C to 50°C/-4°F to 122°F) with rubber boot according to MIL STD 810 H.
Tumbles	500 0.5m/1.6 ft tumbles at room temperature without protective boot, meets and exceed IEC 60068-2-32 Procedure 2 specification. 500 1m/3.2 ft tumbles at room temperature with rubber boot, meets and exceed IEC 60068-2-32 Procedure 2 specification.
Sealing	IP65 and IP67
Chemical Resistance	General purpose chemical cleansers: "Water solution of Sodium Hypochlorite" "Windex Multisurface / Glassex with ammonia" "Formula 409, Glass and Surface cleaner / Glassex with ammonia" "Ethyl alcohol" "Isopropyl alcohol" "Hydrogen peroxide"
Temperature	Operating: -10 to 50 °C / 14 to 122 °F Storage/Transport: -40 to 70 °C / -40 to 158 °F
ESD	15kV air discharge / 8kV contact discharge

PHYSICAL CHARACTERISTICS

Dimensions	165 x 76.7 x 13.5 mm / 6.49 x 3.0 x 0.53 in
Primary Display	6.0 inch LTIPS in 18:9 format - FHD+ resolution 1080x2160; LED backlight; 450 NITS
Keys	Physical Keys: 2 side scan keys; PTT; Power On/Off; Volume Up/ Down; 3 Android soft keys
Touch Panel	Touch Screen: 5 points multi-touch capacitive panel with hardened Gorilla Glass 7 and optical bonding; Support for gloves and stylus; water drops rejection and anti-fingerprint surface finishing
Weight	With Battery: 245 g/8.6 oz

READING PERFORMANCE

Camera	Rear Camera: Resolution: 13 megapixel; Auto focus Illumination: User controllable LED flash (torch mode); Front Camera: Resolution: 8 megapixel; Fixed focus
Scan Engine	Halogen™ DE2121-DL 1D/2D scan engine; Datalogic's 'Green Spot' for good-read feedback;

SENSORS

Vibration	Software programmable for duration and intensity
Accelerometer	3-Axis accelerometer to detect orientation
Gyroscope	Senses angular velocity
Ambient Light	Auto adjusts display backlight
Proximity	Auto deactivates display when close to face
Magnetometer	e-compass for direction and orientation detection
Barometer	Atmospheric pressure / Z-location (Memor 17 only)

INTERFACES

Interfaces	High Speed USB 3.2 gen1 Host and Client (Type-C); Super Speed USB 2.0 (Type-C, Bottom I/O)
-------------------	--

AUDIO

Microphones	2 mics, with noise cancellation
Loudspeaker	Speaker for handsfree calls and audio application
Receiver	Speaker for voice calls

SAFETY & REGULATORY

Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use.
Environmental Compliance	Complies to EU RoHS

SOFTWARE

DATALOGIC MOBILITY SUITE - Discover more on: datalogic.github.io

Protection	Shield - Android Security Updates; Launcher - to lockdown device to kiosk mode; Enterprise Browser - to web-browse only to a set of approved URLs; Integrity KIT - to safeguard HW interfaces
Configuration	Scan2Deploy Studio - to configure and stage device, OEMConfig - for UEM/EMM Compatibility, AE QR Code Enrollment - for easy EMM/UEM enrollment
Development	SDKs (Java, Kotlin, Xamarin, .NET MAUI JavaScript), Visual Formatter - a no-code platform for barcode formatting, Wedge - a configurable barcode scanning input method
Optimization	SoftSpot - a draggable touch scanner trigger; Logger - to collect advanced device events log; Wi-Fi Guard - to collect Wi-Fi data and statistics; Battery Manager to select from different charging policies; QuickBoard - A customizable enterprise virtual keyboard to enhance productivity and adapt to specific application contexts; Snap OCR - Rear or scanner camera digitizes text, streamlining data entry and label parsing
Additional Features	
Provisioning	Android Zero-Touch, Android Enterprise QR Code, NFC Bump, EMM Token, DPC Identifier enrollment
UEM/EMM	SOTI MobiControl, VMware Workspace One, Microsoft Intune, 42Gears Sure MDM, Ivanti Neurons, Ivanti Avalanche, and any OEM Config compliant UEM/EMM
Terminal Emulator and PTT Compatibility Highlight	Ivanti Velocity, StayLinked Smart TE, Zello PTT

SYSTEM

SIM Slots	1 Nano SIM; 1 eSIM
Expansion Slots	1 Micro SD card (up to 2TB)
Memory	RAM Model 6GB: 6 GB on-chip RAM, plus an optional 2 GB SWAP Memory (using flash storage as extra RAM, activated through a setting). UFS Flash Storage: 64 GB (both models)
Microprocessor	Qualcomm QX4490 Octa-core 2.4 GHz
Operating System	Android 13, upgradeable to Android 18
Real-Time Clock	Time and date stamping under software control
WARRANTY	
Warranty	1-Year Factory Warranty