

Nicht mehr verfügbar! Wir empfehlen: Denso MC-83



Denso BHT-1800 – Geneigter Scankopf erlaubt einfaches Scannen

- ✓ Geneigter Scankopf für einfaches Scannen
- ✓ Robustes Design gegen Stürze, Wasser, Staub und extreme Temperaturen geschützt
- ✓ Android-Betriebssystem für optimale Performance
- ✓ Übertragung der Daten per WLAN, Bluetooth oder optional 4G LTE
- ✓ Lange Akkulaufzeit für den ununterbrochenen Einsatz auch in langen Schichten

Eigenschaften

Display: 5 Zoll, 1280 x 720 px, Asahi Dragontrail Pro Glas

Tasten: 4 (programmierbare) Tasten, 2 Auslöser

Betriebssystem: Android 7 / 8

Lesbare Codes: 1D und 2D, NFC Cards

Akku: ca. 12 - 24 h, Wireless Charging

Anbindung: WLAN, Bluetooth, 4G LTE, USB

Zusätzliche Features: GPS, 8MP Kamera, Touch Trigger

Dockingstation Schnittstellen: USB, LAN

Schutz: IP67, bis 2,5 m sturzsicher

Betriebstemperatur: -20 – 50 °C

Abmessungen (B x L x H): 80 x 158 x 32 mm

Gewicht: 275 g

Optionales Zubehör

Handschlaufe

Hüfttasche

**Aktiv Halterung mit Zigarettenanzünder-
Stecker - Brodit CC-1800**

Stylus Stift

USB Ladeschuh

BHT1800-LS

4-fach Akkuladestation

1- & 4-fach Dockingstation

Displayschutzfolie

Type		BHT-1800 QWBG-1	
OS		Android 7.1.2 (Nougat) / Android 8.1 (Oreo)*9	
CPU		1.3 GHz Quad-core	
Memory	RAM	2 GB	
	Flash ROM	16 GB	
Display	Number of dots*1	5.0 inch HD (1280x720 pixels)	
	Display system	Liquid crystal dot matrix display (colour)	
	Backlight	White LED	
Scanner	Reading system		Area sensor
	Readable codes	2D Codes	QR Code, MicroQR Code, SQRC®, PDF417, MicroPDF417, MaxiCode, DataMatrix (ECC200), GS1 Composite
		1D Codes	EAN-13/8(JAN-13/8), UPC-A/E, UPC/EAN (with add-on), Interleaved 2 of 5 (ITF), Standard 2 of 5 (STF), CODABAR (NW-7), CODE39, CODE93, CODE128, GS1-128 (EAN-128), GS1 DataBar (RSS)
	Minimum resolution	2D Codes	0.167 mm
		1D Codes	0.125 mm
	Scanning reference position		100 mm
	Marker		Area guide marker
	Scan confirmation		Visual (blue LED), acoustic (speaker), haptic (vibration)
Keypad	Number of keys		5 keys (incl. power key) + 2 trigger keys
Touch panel		Asahi Dragontrail™ Pro - wet touch / gloved fingertip / stylus	
GPS		A-GPS/GLONASS	
Commu- nication	Wireless LAN*2	Compatible standards	IEEE802.11a/b/g/n compliant
		Frequency band	IEEE802.11a/n: 5.2 GHz, 5.3 GHz, 5.6 GHz band, IEEE802.11b/g/n: 2.4 GHz band
		Trans- mission distance*3	IEEE802.11a: indoors = approx. 50m, IEEE802.11b/g/n: indoors = approx. 75m, outdoors = approx. 200m
		Trans- mission speed*3	IEEE802.11b: 11/5.5/2/1 Mbps, IEEE802.11a/g: 54/48/36/24/18/12/9/6 Mbps, IEEE802.11n: 65/58.5/52/39/26/19.5/13/6.5 Mbps
		Access method	Infrastructure mode
		Security	Encryption: WEP(40/128)/TKIP/AES, WPA authentication: WPA/WPA2, User authentication: PSK/EAP-TLS/PEAP
	WWAN	Compatible standards	4G LTE / 3G / GSM, VoLTE
	Bluetooth®		V4.1+EDR/LE (Compatible Profile: GAP/SDAP/HSP/SPP/GOEP/OPP/HFP(AG1.5)/PAN/A2DP/AVRCP/GAVDP/HID/PBAP/HOGP/MAP/GATT)
	USB (DNWA Connector)		USB 2.0
Card slot		Micro SDHC / SDXC, nanoSIM x2	
Power supply	Power	Lithium-ion battery (2900 mAh)	
	Operating time*4	12 hours*5	
NFC		—	
Wireless charging		—	
Camera	Rear	8 MP Autofocus	
	Front	—	
Environ- mental require- ments	Operating temperature*7	-20° to 50° C	
	Protection rating	IP67	
	Drop resistance*8	1.5 m x 60 times or more, 2.5 m	
Weight (incl. battery)		Approx. 275 g	