

Nicht mehr verfügbar! Wir empfehlen: [Zebra ET60 / ET65](#)



Zebra L10 – Modernste Technologie mit vielen Optionen

Für den anspruchsvollen Einsatz in Industrie, Transport und Wartung

Mit einer IP65-Zertifizierung ist das Zebra L10 gegen Staub und Wasser geschützt. Es übersteht Stürze aus bis zu 1,8 Metern Höhe und erfüllt den MIL-STD-810G-Standard. Der Betriebstemperaturbereich liegt zwischen -20 °C und 60 °C, was den Einsatz in verschiedenen Umgebungen ermöglicht.

Umfangreiche Konnektivität: WLAN, Bluetooth, Mobilfunk, USB und RS232

Ermöglicht eine nahtlose Integration in verschiedene IT-Infrastrukturen und gewährleistet eine stabile Datenübertragung.

Zahlreiche Hardware-Optionen für zielgerichtete Konfiguration

Es stehen mehrere Prozessoren zur Auswahl, Intel i7, i5 und N4200, der Arbeitsspeicher kann zwischen 4 GB und 16 GB RAM variieren, während der interne Speicher von 64 GB bis zu 1 TB SSD reicht.

10,1 Zoll Display mit 2K Auflösung, optional mit besonders starker Leuchtkraft

Das bruchfeste Display mit 2K-Auflösung (1920 x 1200 Pixel) stellt selbst kleinste Details scharf und kontrastreich dar. Optional ist eine besonders starke Leuchtkraft verfügbar, die Arbeiten im direkten Sonnenlicht erleichtert. Das Touch-Display kann zuverlässig mit Handschuhen oder nassen Händen bedient werden.

Umfangreiches Zubehör, wie Akku mit 27 Stunden Laufzeit

Für spezifische Anforderungen steht umfangreiches Zubehör zur Verfügung, wie beispielsweise ein Akku mit bis zu 27 Stunden Laufzeit, stationäre und Fahrzeug-Dockingstationen sowie Tastaturen. Zudem können Datenerfassungsoptionen wie NFC, RFID und Barcode-Scanner integriert werden.

Eigenschaften

Display: 10,1 Zoll, 1920 x 1200 px

Betriebssystem: Windows 10

CPU: Intel i7 / i5 / N4200

Speicher: 4 - 16 GB RAM, 64 GB - 1 TB SSD

Akku: bis zu 27 h, hot swappable

Netzwerkverbindungen: WLAN, Bluetooth, Mobilfunk, USB, RS232

Zusätzliche Features: Kameras, GPS

Schutz: IP65, bis 1,8 m sturzsicher, MIL-STD-810G

Betriebstemperatur: -20 – 60 °C

Abmessungen (B x L x H): 280 x 195 x 22 mm

Gewicht: 1,2 kg

Optionales Zubehör

Datenerfassung: NFC, RFID, Barcode Scanner

Tastaturen

Dockingstations stationär / Fahrzeug

High Capacity Akkus

Ständer

Stromanbindungen

Eingabestifte

Antennen

Handschlaufen, Schultergurte

Physical Characteristics

Dimensions	XSLATE: 11.0 in. L x 7.7 in. W x 0.88 in. D 280.8 mm L x 195.2 W mm x 22 mm D XPAD: 11.0 in. L x 10.0 in. W x 0.88 in. D 280.8 mm L x 255.9 W mm x 22 mm D XBOOK: 11.0 in. L x 8.3 in. W x 2.36 in. D 280.8 mm L x 210.8 W mm x 60 mm D
Weight	XSLATE: 2.8 lbs/1.3 kg ² XPAD: 3.1 lbs/1.4 kg ² XBOOK: 4.63 lbs/2.1 kg ²
Frame	Magnesium alloy internal frame with external elastomer corner bumpers
Display	10.1 in. 2K resolution display WUXGA 1920 x 1200 (16:10) - Standard 500 Nit capacitive - View Anywhere® 1000 Nit capacitive - View Anywhere 1000 Nit with active Wacom® digitizer Corning® Gorilla® Glass 3 Capacitive 10-point touch Contrast ratio = 800 : 1 Wide viewing angle ±89° Standard user replaceable anti-glare screen protector — 3H hardness Auto-sensing standard, glove and wet touch Night vision mode supported on Active View Anywhere Display only
Graphics	N4200 CPU - Intel® UHD Graphics 505 Core i5 & i7 CPUs - Intel® UHD Graphics 620
Battery Life & Power	Standard battery: up to 10 hours ³ Extended battery: up to 27 hours ³ Battery charge time: - Standard battery: 2.75 hours with system off ⁴ - Extended battery: 3.25 hours with system off ⁴ Standard bridge battery (1 minute swap time) Hot swap battery feature comes standard Input Voltage: 12-20V, AC Adapter: 19V
Ports/Connectivity	Docking connector (2) USB 3.0 ports USB Type-C port (USB 2.0, USB 3.0, Display Port out) 3.5 mm audio output (stereo out, mono in) RJ-45 ethernet port Dual Nano SIM (4FF) Micro-SDXC
Expansion Slot	Micro-SDXC
Integrated Options	NFC Optional 1D/2D barcode reader (XPAD only) Optional True RS232 serial, or Optional HDMI-In, or Optional CAC / Smart Card reader, or Optional UHF RFID reader (AEI)
Rugged Keyboard	Included with XBOOK: backlit; IP65; 3.2 ft./1 m drop specification; kick strap/stand (rugged keyboard is optional for the XSLATE and XPAD)
Security	Integrated fingerprint reader Trusted Platform Module (TPM) 2.0 Optional CAC / Smart Card reader
Status Indicators	System status, battery status, camera active, SSD activity
Audio	Intel High Definition audio Realtek® HD Codec RealTek noise cancellation Multi-directional array microphone - 2 microphones (2 front facing array mic) XPAD: 1 front facing speaker XSLATE/XBOOK: 1 rear facing speaker
Performance Characteristics	
Operating System	Windows® 10 Pro 64-bit
Processor	8th Generation Intel® Core™ i7 vPro™ processor – 8650U (LPDDR3, 1.90 GHz with turbo frequency to 4.20 GHz) 8th Generation Intel® Core™ i5 vPro™ processor – 8350U; (LPDDR3, 1.70 GHz with turbo frequency to 3.60 GHz) 8th Generation Intel® Core™ i5 processor – 8250U; (LPDDR3, 1.60 GHz with turbo frequency to 3.40 GHz) Intel® Pentium® processor N4200; (LPDDR4, 1.10 GHz with turbo frequency to 2.50 GHz)

Memory	4 GB (Pentium N4200 only) 8 GB (Pentium N4200 & Core i5 8250U only) 16 GB (Core i5 vPro 8350U & Core i7 vPro 8650U only)
Storage Options	N4200 CPU: Core i5 & i7 CPUs: 64 GB SATA SSD 128 GB PCIe SSD 128 GB SATA SSD 256 GB PCIe SSD 256 GB SATA SSD 512 GB PCIe SSD 512 GB SATA SSD 1TB PCIe SSD
User Environment	
Operating Temperature	-4° F to 140° F/-20° C to 60° C; MIL-STD-810G
Storage Temperature	-22° F to 158° F/-30° C to 70° C; MIL-STD-810G
Thermal Shock	-22° F to 158° F/-30° C to 70° C within five (5) minutes, non-operating; MIL-STD-810G
Drop Specification	MIL-STD-810G: 6 ft./1.83 m drops to plywood over concrete 4 ft. drops to concrete
Sealing	IP65
Hazardous Environments	C1D2 (Class 1 Division 2) for hazardous locations ⁵
Vibration	Minimum integrity non-operating, composite wheel operating; MIL-STD-810G
Shock	40G operating; MIL-STD-810G
Humidity	3% to 95% non-condensing, -22° F to 140° F/-30°C to 60°C, 5 cycles of 48Hr; MIL-STD-810G
Water Proofing	Method 506.5 - Procedure I, wind speed 40 mph, 4 inches per hour, 4 sides; MIL-STD-810G
Blowing Sand	20M/S, rate 1.1g/m3 (+/- .3g) at high temperature of 140° F/60° C; MIL-STD-810G
Blowing Dust	Velocity 8.9M/s dust concentration 3.9 g/m3 at high temperature of 140° F/60° C; MIL-STD-810G
Fluid Contamination	50/50 solution of water and bleach, 50/50 solution of water and hydrogen peroxide, diesel fuel, mineral based oil, Lysol disinfectant, denatured alcohol, isopropyl alcohol; MIL-STD-810G
Altitude	Operating: 50,000 ft./15,240 m; MIL-STD-810G
Data Capture	
Camera	13 MP rear camera; 2 MP front camera
NFC	Optional
RFID	Optional UHF RFID Reader (AEI)
Barcode Scanner	Optional on XPAD only: SE4710 1D/2D imager ⁵
Wireless WAN/GPS Data (Cellular)	
Radio Frequency Bands	Optional internal wireless (one expansion slot) with choice of: • Sierra Wireless EM7565, 4G LTE with GNSS (GPS + GLONASS + Galileo + BeiDou) • Sierra Wireless EM7511, LTE-Advanced with GNSS receiver (GPS + GLONASS, BeiDou, and Galileo) • Discrete GNSS, Navsys Technology (u-blox) GPS + GLONASS with SBAS (WAAS, EGNOS and MSAS) Optional Pass-Through antenna includes 5 ports for MIMO WWAN, MIMO WLAN and GPS AT&T FirstNet Ready certification Verizon PNTM certification CRS Capable (Band 48) - EM7511 Configurations
FirstNet Ready Models	Sierra Wireless EM7511: LTE-Advanced with GNSS receiver (GPS, GLONASS, BeiDou, and Galileo satellite systems supported)
Wireless LAN (WiFi)	
Radio	Intel® Dual Band Wireless-AC 8265 Wi-Fi® plus Optional Pass-Through antenna includes 5 ports for MIMO WWAN, MIMO WLAN and GPS
Wireless PAN (Bluetooth)	
Bluetooth	Class 1, Bluetooth® 4.2 (EDR + BLE)
-	